

## hushcore | PRODUCT DESCRIPTION

HushCore provides it all in one great looking package. HushCore's High Performance Core (HPC) is constructed with first quality virgin vinyl materials that provide a rigid and waterproof core. Add to that Hushcore's attached acoustical cork backing and you have the complete package when sound control, resistance to scuffing and scratching, and the ability for quick and consistent installations are needed. HushCore's high performance construction and protective Cobalt Guard finish provides superior resistances to scratching, scuffing, and indentations while helping hide minor substrate irregularities. With a LIFETIME residential warranty and a 10-year commercial warranty, HushCore is the perfect solution for your flooring needs.

## hushcore | FEATURES

- |                                  |  |
|----------------------------------|--|
| 100% Recyclable & Phthalate Free | Excellent Sound Control Performance        |
| Waterproof                       | Qualifies for LEED Credits                 |
| Enhanced Cobalt Guard Finish     | FloorScore Certified                       |
| High Performance Core            | Limited Lifetime Residential Wear Warranty |
| Attached Acoustical Backing      | 10 Commercial Warranty                     |

## hushcore | TECH DATA

- |   |                                   |
|---|-----------------------------------|
| Nominal Dimensions  | 7" x 48" Planks                   |
| Gauge   | 6.5mm                             |
| Acoustical Cork Backing Gauge   | 1mm                               |
| Wear Layer Thickness  | 20 mil / 0.5mm                    |
| Quantity Per Carton   | 10 Planks / 23.2 Sq Ft per Carton |
| ASTM E 648 Critical Radiant Flux  | Class I, >.45 w/cm <sup>2</sup>   |
| ASTM E 662 - Smoke Density  | Passes <450                       |
| ASTM E 970 - Static Load Limit  | .001" @ 250 lbs.                  |
| ASTM F 925 - Chemical Resistance  | Excellent                         |
| ASTM F 1515 - Light Stability   | Very Slight                       |
| ASTM F 1514 Heat Stability  | Very Slight                       |
| ASTM F 2199 Dimensional Stability                                       | < 1% change                       |
| ASTM E 90 / E 492 Acoustical Rating 6" Concrete (No Ceiling)            | IIC 54                            |
| Additional Sound Testing - Acoustical Rating 6" Concrete (With Ceiling) | IIC 65 STC 60                     |