

## katanga | PRODUCT DESCRIPTION

Katanga brings you high performance flooring options with protective Cobalt Guard finish, providing superior scratch, scuff, and indentation resistance. Made with design and budget in mind, Katanga is your everyday flooring choice that combines contemporary style and durability for the highest foot traffic areas. Katanga Loose Lay has an attached performance pad that provides excellent sound control properties. Katanga LL is great for installations next to or butting to carpet and carpet tile. Simplicity in loose lay installation provides the ability to complete installation projects quickly, install over certain existing floors, and have removable and easily replaceable floors. Loose Lay can be installed via standard loose lay installation methods or fully adhered with approved adhesive

## katanga | FEATURES

- |   |   |
|---|---|
| 100% Recyclable & Phthalate Free                | Excellent Sound Control Performance       |
| Enhanced Cobalt Guard Finish                    | Qualifies for LEED Credits                |
| Non-Skid Backing                                | FloorScore Certified                      |
| Attached Performance Pad                        | Lifetime Residential Warranty             |
| Loose Lay or Full Adhesion Installation Options | 10 Commerical Warranty - No Rolling Loads |

## katanga | TECH DATA

Nominal Dimensions	7" x 48" Planks
Gauge	5mm
Performance Pad Gauge	1.25mm
Wear Layer Thickness	20 mil / 0.5mm
Quantity Per Carton	10 Planks / 23.36 Sq Ft per Carton
ASTM E 648 Critical Radiant Flux	Class I, >.45 w/cm <sup>2</sup>
ASTM E 662 - Smoke Density	Passes <450
ASTM E 970 - Static Load Limit	Passes
ASTM F 925 - Chemical Resistance	Passes
ASTM F 1515 - Light Stability	Passes
ASTM F 510 Wear Resistance	Wear Group: T
ASTM F 1914 Residual Indentation	Passes
ASTM F 2199 Dimensional Stability	Passes
DIN 51130 Slip Resistance	R10
ASTM E 90 / E 492 Acoustical Rating 6" Concrete (No Ceiling)	IIC 53, STC 54, Delta IIC 20
Additional Sound Testing - Acoustical Rating 6" Concrete (With Ceiling)	IIC 57