



HIGH PERFORMANCE FLOORING WITH DESIGN IN MIND

	D42 400	D. i.e. He	D12 440
Biscay	P12-409	Brindle	P12-419
-			
Cascade	P12-410	Drizzle	P12-400
			30)
Dusky	P12-405	Fawn	P12-401
	S THE WHAT		
Gravel	P12-411	Grounded	P12-418
		3/1	
Hydro	P12-407	Mallard	P12-402
Mirage	P12-417	Mist	P12-413
The state of the s			
Nougat	P12-403	Sepia	P12-415
Cabiny	D12 404	Thunder	
Sphinx	P12-404	Thunder	P12-406
Vapor	P12-412	Wicker	P12-408
Willow	P12-416	Wren	P12-414

PETROUS RIGID CORE

FEATURES/BENEFITS

- 10 Year Light Commercial Warranty
- 35 Year Residential Warranty
- Waterproof
- High impact resistant, dependability and clean designs
- Easy click together installation
- Superior dimensional stability
- Attached acoustical pad for excellent sound reduction
- Floorscore® Certified
- ASTM E90 / E492 Acoustical Rating
 - 6" Concrete Slab IIC 55, STC 52

SPECIFICATIONS

Nominal 7" x 48" Planks, Micro-Bevel Size: 4.5mm (3.5mm + 1mm IXPE backing) Gauge:

Wear Layer: 12mil

Cobalt Guard (enhanced polyurethane) Finish:

Method of Install: Floating (Click System)

Item/Color Identifier: P12-### S/F per Carton: 28.657

Cobalt Guard

Excellent stain, abrasion, and fade resistance with anti-bacterial effect, easy to maintain and no need to wax.

Wear Layer

A transparent vinyl wear layer provides protection against scuffs and abrasions, even in demanding commercial environments.

Decorative Film Laver

Printed film delivers the beauty and realism of natural wood, stone, fabric etc. with vivid clarity.

Rigid Core Layer

Extruded SPC structural core, 100% waterproof, rigid, strong, and dimensionally stable.

IXPE Pad for Comfort and Acoustics

A pre-attached underlayment that minimizes both reflected and transmitted sound, is shock-absorbing, provides warmth and comfort underfoot and helps further conceal minor subfloor imperfections.



