



KATANGA

2MM 12MIL SPECIFICATIONS & TESTING

Katanga 2mm 12mil LVT brings you high performance flooring options with protective Cobalt Guard finish, providing superior scratch, scuff, and indentation resistance. Made with design and budget in mind, Katanga is your everyday flooring choice that combines contemporary style and durability for the highest foot traffic areas.



Superior Scuff & Scratch Resistance



Qualifies for LEED Credits



100% Recyclable & Phthalate Free



Enhanced Polyurethane Cobalt Guard Finish

SPECIFICATIONS

Nominal Size	7"x48" Wood Visual 12"x24" Tile Visual
Overall Thickness	2mm
Wearlayer Thickness	12mil
Edge	Square; Non-Bevelled
Finish	Cobalt Guard
Installation Method	Glue Down
Item/Color Identifier	K12-###
Sq. Ft. Per Carton	7"x48": 51.39 Sq. Ft. 12"x24": 52.74 Sq. Ft.
Residential Warranty	20 Year
Commercial Warranty	7 Year Light





KATANGA

2MM 12MIL SPECIFICATIONS & TESTING

TESTING

Test	Description	Result
ASTM F 970	Static Load Limit	Pass
ASTM E 648	Critical Radiant Flux	Class I, >.45w/cm2
ASTM F 925	Chemical Resistance	Pass
ASTM F 1515	Light Stability	Pass
ASTM F 510	Wear Resistance	Wear Group: T
ASTM F 2199	Dimensional Stability	Pass
ASTM E 662	Smoke Density	Pass, <450
ASTM F 1914	Residual Indentation	Pass
DIN 51130	Slip Resistance	R10

