



# KATANGA

## 3MM 20MIL SPECIFICATIONS & TESTING

Katanga 3mm 20mil LVT brings you high performance flooring options with protective Cobalt Guard finish, providing superior scratch, scuff, and indentation resistance. Made with design and budget in mind, Katanga is your everyday flooring choice that combines contemporary style and durability for the highest foot traffic areas.



Superior Scuff & Scratch Resistance



Qualifies for LEED Credits



100% Recyclable & Phthalate Free



Enhanced Polyurethane Cobalt Guard Finish

### SPECIFICATIONS

|                       |   |
|-----------------------|---|
| Nominal Size          | 7"x48" Wood Visual<br>12"x24" Tile Visual       |
| Overall Thickness     | 3mm   |
| Wearlayer Thickness   | 20mil   |
| Edge                  | Square; Non-Bevelled                            |
| Finish                | Cobalt Guard                                    |
| Installation Method   | Glue Down                                       |
| Item/Color Identifier | K320-###  |
| Sq. Ft. Per Carton    | 7"x48": 35.04 Sq. Ft.<br>12"x24": 37.98 Sq. Ft. |
| Residential Warranty  | Lifetime  |
| Commercial Warranty   | 10 Year   |





# KATANGA

## 3MM 20MIL SPECIFICATIONS & TESTING

### TESTING

| Test        | Description           | Result              |
|-------------|-----------------------|---------------------|
| ASTM F 970  | Static Load Limit     | Pass                |
| ASTM E 648  | Critical Radiant Flux | Class I, >.45 w/cm2 |
| ASTM F 925  | Chemical Resistance   | Pass                |
| ASTM F 1515 | Light Stability       | Pass                |
| ASTM F 510  | Wear Resistance       | Wear Group: T       |
| ASTM F 2199 | Dimensional Stability | Pass                |
| ASTM E 662  | Smoke Density         | Pass <450           |
| ASTM F 1914 | Residual Indentation  | Pass                |
| DIN 51130   | Slip Resistance       | R10                 |

