



KATANGA

5MM 20MIL W/ ATTACHED PERFORMANCE PAD SPECIFICATIONS & TESTING

Katanga 5mm 20mil LVT w/ Attached Performance Pad brings you high performance flooring options with protective Cobalt Guard finish, providing superior scratch, scuff, and indentation resistance. Made with design and budget in mind, Katanga is your everyday flooring choice that combines contemporary style and durability for the highest foot traffic areas.



Superior Scuff & Scratch Resistance



Qualifies for LEED Credits



100% Recyclable & Phthalate Free



Enhanced Polyurethane Cobalt Guard Finish

SPECIFICATIONS

Nominal Size	7"x48" Wood Visual 12"x24" Tile Visual
Overall Thickness	5mm
Wearlayer Thickness	20mil
Edge	Square; Non-Bevelled
Finish	Cobalt Guard
Installation Method	Loose Lay or Glue Down
Item/Color Identifier	KP5-###
Sq. Ft. Per Carton	7"x48": 23.36 Sq. Ft. 12"x24": 21.10 Sq. Ft.
Residential Warranty	Lifetime
Commercial Warranty	10 Year (no rolling loads)





KATANGA

5MM 20MIL W/ ATTACHED PERFORMANCE PAD SPECIFICATIONS & TESTING

TESTING

Test	Description	Result
ASTM F 970	Static Load Limit	Pass
ASTM E 648	Critical Radiant Flux	Class I, >.45w/cm2
ASTM F 925	Chemical Resistance	Pass
ASTM F 1515	Light Stability	Pass
ASTM F 510	Wear Resistance	Wear Group: T
ASTM F 2199	Dimensional Stability	Pass
ASTM E 662	Smoke Density	Pass, <450
ASTM F 1914	Residual Indentation	Pass
ASTM D2047	Slip Resistance	>0.6
ASTM E90 / E492 (6" Concrete Slab / No Ceiling)	Acoustical Rating	IIC 53 STC 54
ASTM E90 / E492 (18" Open Truss)	Acoustical Rating	IIC 58 STC 61 HIIC 52

